

Novichem Co.

Your Chemical Partner

P.O. Box: 14476-43971, Tehran - IRAN
Phone : +98-21-88329799 E-mail : info@novichem.co
Fax : +98-21-88329799 Web : www.novichem.co

PROWASH W Soaking and wetting agent

DESCRIPTION

Prowash W is an anionic soaking and wetting agent which can be applied in various stages of leather processes.

TECHNICAL SPECIFICATIONS

Appearance	: Yellow liquid
Nature	: Alkyl aryl sulfonate
Solid content	: 45 ± 1 %
Charge	: Anionic
pH (1:10 solution)	: 7 ± 1
Packing	: 100 kg drums or IBC tanks

APPLICATIONS

Prowash W can be used even in low dosage which results in acceleration of the soaking and wetting operation. It reduces the friction in all drum processing, especially when short floats are used by the tannery.

Prowash W should be applied in the lime process after the hair has been removed. The quantity applied depends on the material and the position in the process.

Soaking:	Up to 0.5% based on raw weight
Wetting back (Retannage):	0.2-0.5% based on shaved weight

The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purpose. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.