

## Novichem Co.

Your Chemical Partner

P.O. Box: 15886-13941, Tehran / IR

Phone : +98-21-88329799 (Hunting)

Fax : +98-21-88329799

E-mail : info@novichem.co

Web : www.novichem.co

## ACRYNTEX H-1530 Binder for non-wovens

### DESCRIPTION

**Acryntex H-1530** is a textile industry binder based on poly vinyl acetate homopolymer and is used in the manufacture of non-woven interlinings, personal hygiene such as wipes and cleaning cloths.

### TECHNICAL SPECIFICATIONS

Appearance Solid	: Milky White emulsion
Content (%)	: 50 ± 1
Viscosity (25°C) cps.	: 25000 - 33000
pH	: 5 - 6
MFFT (°C)	: 8
Density (gr/cm <sup>3</sup> )	: 1.28
Packing	: 200 Kg steel drums

### APPLICATION

**Acryntex H-1530** can be applied by spray bonding with water by means of nozzles, gives very good distribution of resin binder on the surface and uniform penetration, thus improving the resilience and durability to washing.

In addition to the spray bonding system as described above, the binder can also be applied by padding. The self crosslinking is actualized in 3 minutes at a temperature 120 - 140 °C. It has an excellent adhesion to both natural and synthetic fibers.

The information and recommendations in this publication are to the best of our knowledge reliable. However, nothing herein is to be construed as a warranty or representation. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purpose.

Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed.